

Fujitsu, years of experience

Relays



shaping tomorrow with you

Content

ABOUT FUJITSU COMPONENTS	
■ Fujitsu, years of experience	Page 2

PRODUCT LINE-UP	
■ Automotive relays	Page 3
■ Power relays	Page 9
■ Signal relays	Page 18
■ High frequency relays	Page 21
■ Solid state relays	Page 22

About Fujitsu Components

Fujitsu, years of experience

Over the years Fujitsu Components has made its name in the components and devices market with a complete product line-up of relays, thermal printers, touch panels and wireless modules. All adapted to the requirements of the market.

Supplying high quality and reliable components is only one of Fujitsu's strengths. Another strength is providing a high level of customer support service. Designed to meet our commitment to customers and to develop long lasting working relationships, our support includes: customer design facility, full technical back-up, applications advice, central warehousing and distribution, full literature and documentation and a specialist network of distributors.





Fujitsu Components product experts have built a wealth of knowledge through their years of experience. They are pleased to share their knowledge with customers and offer technical support.

Fujitsu relays





Quality is the key word describing Fujitsu Components' relays. The relay product range covers automotive, power, signal, high frequency and solid state relays. The relays are available in a wide range of variations such as slim line, ultra quiet and low power consumption. Through continued research and development Fujitsu keeps expanding its product range.

Visit emea.fujitsu.com/components to find out more about our business activities.






Automotive relays (25A)

SERIES NAME		FTR-G1	FTR-P3	FTR-P5	FTR-P2
■ Dimensions W x L x H (mm)		 6.6 x 13.7 x 13.5	 7.2 x 17.4 x 13.5	 9.7 x 20.4 x 16.7	 16.5 x 21.0 x 18.0
■ Weight (approx.)		3.5 g	5.0 g	7.0 g	13.0 g
■ Contact form		1 c	1 c	1 c	H-bridge
■ Contact current rating		25A	25A	25A 1Hr	25A 1Hr
■ Expected life on load example 14 VDC Inrush 25A, power window motor (1 operation: 1 forward and 1 reverse) 100x10 ³ ops. 14VDC Inrush 19A, 12A break power window motor 200x10 ³ ops. 14VDC Inrush 20A, door lock locked motor 100x10 ³ ops. Inrush 35A		14 VDC, free motor load Inrush 17A 300x10 ³ ops. 14 VDC, 25A locked motor 100x10 ³ ops. Inrush 35A	14 VDC, free motor load Inrush 17A 300x10 ³ ops. 14 VDC, 25A locked motor 100x10 ³ ops. Inrush 35A	14 VDC, 30A free motor load 300x10 ³ ops. 14 VDC, 25A locked motor 100x10 ³ ops. Inrush 35A	14 VDC, free motor load Inrush 17A 300x10 ³ ops. 14 VDC, 25A locked motor 100x10 ³ ops. Inrush 35A
■ Coil voltage (DC)		9 to 12 V	9 to 12 V	9 to 12 V	9 to 12 V
■ Nominal coil power		0.64 W	0.6 to 0.86 W	0.45 W	0.45 W
■ Dielectric strength	Open contacts	500 VAC	500 VAC	500 VAC	500 VAC
	Coil and contacts	500 VAC	500 VAC	500 VAC	500 VAC
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)					
■ Remarks		- 0.3mm contact gap	- SMC type available - Higher stand-off types available - High temp. versions available - 0.3 or 0.6mm contact gap	- Average acoustic noise level: 50 dB - 0.3mm contact gap	- Average acoustic noise level: 50 dB - Pin compatible with P4 - 0.3mm contact gap





Automotive relays (25A)

SERIES NAME		FTR-P4	FTR-P6	FTR-P7 New design	FBR51/52
■ Dimensions W x L x H (mm)		 14.2 x 17.4 x 13.5	 9.0 x 12.0 x 10.3	 17.0 x 20.8 x 14.0	 12.1 x 15.5 x 13.7
■ Weight (approx.)		10.0 g	3.3 g	7.0 g	6.0 g
■ Contact form		H-bridge	1 c	1 c	1 c
■ Contact current rating		25A	25A	25A	25A
■ Expected life on load example 14 VDC, 25A locked motor 100x10 ³ ops. Inrush 35A		14 VDC, 25A locked motor 100x10 ³ ops. Inrush 35A	14 VDC, 25A locked motor 100x10 ³ ops. Inrush 35A	14 VDC, 25A locked motor 100x10 ³ ops. Inrush 35A	14 VDC, free motor load Inrush 20A 400x10 ³ ops. 14 VDC, 25A locked motor 200x10 ³ ops. (-W1 type) Inrush 60A (80A -WL type) 120W lamp load 100K (-WL)
■ Coil voltage (DC)		9 to 12 V	10 to 12 V	12 V	6 to 12 V
■ Nominal coil power		0.6 W	0.8 W	0.6 W	0.6 W / 0.8 W
■ Dielectric strength	Open contacts	500 VAC	500 VAC	500 VAC	500 VAC
	Coil and contacts	500 VAC	500 VAC	500 VAC	500 VAC
■ Mounting		Through hole	Surface mount	Through hole	Through hole
■ Terminal layout (Bottom view)					
■ Remarks		- SMC type available - High temp. versions available - 0.3 or 0.6mm contact gap	- Average accoustic noise level: 60 dB - 0.25mm contact gap - SMD	- Average accoustic noise level: 45dB	- SMC type available - 0.3/0.6mm contact gap - High temperature types available




Automotive relays (25A~35A)

SERIES NAME		FBR53	FBR57	FBR572/582	FBR51NL
■ Dimensions W x L x H (mm)		 12.1 x 15.5 x 13.7	 14.4 x 20.0 x 16.2	 20.0 x 26.0 x 16.2 (FBR572) 20.0 x 26.0 x 17.0 (FBR582)	 12.1 x 15.5 x 13.7
■ Weight (approx.)		6.0 g	9.4 g	18.0 g	6.0 g
■ Contact form		1u	1 c	1 c x 2	1 c
■ Contact current rating		25A	30A	30A	35A
■ Expected life on load example 14 VDC, 25W resistive load 150x10 ³ ops. 14 VDC, 6 x 21W lamp load 100x10 ³ ops. Inrush 60A Inrush 80A, 40A continuous (-HW type)		14 VDC, 25W resistive load 150x10 ³ ops. 14 VDC, 6 x 21W lamp load 100x10 ³ ops. Inrush 60A Inrush 80A, 40A continuous (-HW type)	28 VDC, 2A locked motor 100x10 ³ ops. 28 VDC, 12A free motor load 500x10 ³ ops. Inrush 70A (-W type)	28 VDC, 12A locked motor 100x10 ³ ops. Wide gap type Maximum break rating locked motor load 32V, 14A 60A inrush	14 VDC, free motor load Inrush 20A 400x10 ³ ops. 14 VDC, 25A locked motor 200x10 ³ ops. (-W1 type) Inrush 60A (80A -WL type)
■ Coil voltage (DC)		9 to 12 V	24 V	24 V	6 to 12 V
■ Nominal coil power		0.6 W	1.5 W	1.5 W / 3.4 W	1.1 W
■ Dielectric strength	Open contacts	500 VAC	500 VAC	500 VAC	500 VAC
	Coil and contacts	500 VAC	500 VAC	500 VAC	500 VAC
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)		Standard 		FBR572  FBR582 	
■ Remarks		- SMC type available - 0.25mm contact gap	- For 24V battery applications - 0.8mm contact gap	- For 24V battery applications - 0.8/1.4mm contact gap	- Dual coil latching - SMC type



Automotive relays (35A~45A)

SERIES NAME		FBR51 (-WF)	FBR53-HW	FBR56-HW	FBR59-HW
■ Dimensions W x L x H (mm)		 12.1 x 15.5 x 13.7	 12.1 x 15.5 x 13.7	 15.0 x 20.0 x 16.5	 15.0 x 20.0 x 16.5
■ Weight (approx.)		6.0 g	6.0 g	13.0 g	13.0 g
■ Contact form		1 a	1 u	1 c	1u
■ Contact current rating		35A	40A	45A	45A
■ Expected life on load example 14 VDC, 80W lamp load 250x10 ³ ops. Inrush 80A Special type for flasher lamp applications. 80W Lamp load			Inrush 80A 100x10 ³ ops.	Inrush 220A Max. carrying current 60A	Inrush 220A Max. carrying current 60A
■ Coil voltage (DC)		6 to 12 V	9 to 12 V	9 to 12 V	8 to 12 V
■ Nominal coil power		0.6 W	0.9 W	0.5 W	0.5 W
■ Dielectric strength	Open contacts	500 VAC	500 VAC	500 VAC	500 VAC
	Coil and contacts	500 VAC	500 VAC	500 VAC	500 VAC
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)			High capacity (-HW type) 	High capacity (-HW type) 	High capacity (-HW type) 
■ Remarks		- SMC type available - 0.3/ 0.6mm contact gap	- SMC type available - High power type	- High power type	- High power type





Automotive relays (100A/150A)

SERIES NAME		FTR-V1	FTR-V4 New design
■ Dimensions W x L x H (mm)		 88.0 x 50.6 x 23.7	 72.0x71.5x22.5
■ Weight (approx.)		115.0 g	120.0 g
■ Contact form		1 a	1 a
■ Contact current rating		150A	100A / 60VDC
■ Expected life on load example		14 VDC, 150A 100x10 ⁶ ops. 230A peak break 1A 14VDC, 1x10 ⁶ ops. Inrush 1200A Capacitor load	Inrush 1200A
■ Coil voltage (DC)		12 V	12 to 48 V
■ Nominal coil power		20.5 W	2.3 W / 4.5 W
■ Dielectric strength	Open contacts	500 VDC	1,000 VAC
	Coil and contacts	500 VDC	4,000 VAC
■ Mounting		Through hole/screw/press-fit	Through hole / screw
■ Terminal layout (Bottom view)			Single winding latching type  Double winding latching type 
■ Remarks		- Contact state diagnostic terminals - High current 12VDC relay	- 60VDC high current relay





Automotive relays (450 VDC, 10A~150A)

SERIES NAME		FTR-E1 New design	FTR-E2 New design	FTR-E3 New design
■ Dimensions W x L x H (mm)		 28.0 x 64.5 x 49.5	 22.0 x 57.0 x 46.3	 63.5 x 73.5 x 73.0
■ Weight (approx.)		80.0 g	40.0 g	640.0 g
■ Contact form		1 a	1 a	1 a
■ Contact current rating	Make	10 A	15A	150 A
	Break	3 A	3 A	150 A
■ Expected life on load example		-	1A 30x10 ³ ops. 3A make & break 10x10 ³ ops.	-
■ Coil voltage (DC)		9 to 12 V	9 to 12 V	9 to 12 V
■ Nominal coil power		-	0.78 W	-
■ Dielectric strength	Open contacts	2,500 V	2,500 V	-
	Coil and contacts	5,000 V	5,000 V	-
■ Mounting		Tab terminals	Tab terminals	Screw / tab terminals
■ Terminal layout (Bottom view)				
■ Remarks		- Contact Fujitsu for details	- Contact Fujitsu for details	- Contact Fujitsu for details






Power relays (3A~5A)

SERIES NAME		NY	JY	FTR-F3	FTR-F4
■ Dimensions W x L x H (mm)		 5.0 x 20.1 x 17.5	 10.0 x 20.0 x 12.8	 7.0 x 20.3 x 15.0	 12.0 x 24.0 x 25.0
■ Weight (approx.)		3.5 g	3.7 g	4.0 g	12.0 g
■ Contact form		1 a	1 a	1 a, 1 c	2 a
■ Contact current rating		3A (5A carry)	(5A carry) 3A 3A 5A 3A 5A	3A, 5A (5A carry)	3A, 5A (5A carry)
■ Minimum switching load (ref.)		5VDC 1mA	100mVDC 0.1mA 5VDC 10mA 5VDC 100mA	5VDC 10mA	5VDC 100mA
■ Contact rating (Resistive load)		3A, 250VAC/30VDC	3A, 250VAC/30VDC 5A, 250VAC/30VDC	3A, 250VAC/30VDC 5A, 250VAC/30VDC	5A, 277VAC/30VDC
■ Coil voltage (DC)		4.5 to 24 V	4.5 to 48 V	5 to 24 V	5 to 48 V
■ Nominal coil power		0.12 W	0.2 to 0.36 W	0.2 W	0.53 W
■ Dielectric strength	Open contacts	750 VAC	750 VAC	750 VAC	1,000 VAC
	Coil and contacts	3,000 VAC	2,000 VAC	4,000 VAC	4,000 VAC
■ Surge strength (Coil and contacts)		5,080 V	4,000 V	10,000 V	10,000 V
■ Expected life	Mechanical	20 x 10 ⁶ ops.	10 x 10 ⁶ ops.	5 x 10 ⁶ ops.	2 x 10 ⁶ ops.
	Electrical (Rated load)	100 x 10 ³ ops. (at 3A, 250VAC, 30VDC) 50 x 10 ³ ops. (at 5A, 250VAC)	100 x 10 ³ ops.	200 x 10 ³ ops.	100 x 10 ³ ops.
■ Safety standards		UL, CSA, VDE	UL, CSA, VDE, SEV	UL, CSA VDE, SEMKO, CQC, NEMKO, DEMKO, FIMKO	UL, CSA VDE, SEMKO, CQC
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)					
■ Remarks		- Socket available (-NYP)	- Socket available	- Right angle versions (1 a) - TV-3, TV-5 rating types available - 1 form c type available	- Flux-free type available - TV-3 rated - 8A version available (FTR-F4R)







Power relays (5A)

SERIES NAME		VE	FTR-MY	FTR-F2	FTR-F4G
■ Dimensions W x L x H (mm)		 10.5 x 20.5 x 20.5	 5.0 x 20.0 x 12.0	 11.0 x 24.0 x 25.0	 12.7 x 28.7 x 25.2
■ Weight (approx.)		8.0 g	2.5 g	13.0 g	18.0 g
■ Contact form		1 a, 1 c	1 a	1 a	2 a
■ Contact current rating		(7A carry) 5A (3A*) 5A (3A*)	5A	5A (5A carry)	5A
■ Minimum switching load (ref.)		5VDC 10mA 5VDC 100mA	5VDC 1mA	5VDC 100mA	5VDC 100mA
■ Contact rating (Resistive load)		VE-() H5 5A, 250VAC VE-() H 3A/5A, 250VAC	5A, 250VAC/30VDC	5A, 250VAC/30VDC	5A, 250VAC
■ Coil voltage (DC)		5 to 48 V	4.5 to 24 V	5 to 48 V	5 to 48 V
■ Nominal coil power		0.25 to 0.36 W	0.11 W	0.25 to 0.53 W	0.8 W
■ Dielectric strength	Open contacts	750 VAC (1 c) 1,000 VAC (1 a)	750 VAC	1,000 VAC	1,000 VAC
	Coil and contacts	2,000 VAC	3,000 VAC	4,000 VAC	5,000 VAC
■ Surge strength (Coil and contacts)		4,000 V / 6,000 V	5,080 V	10,000 V	10,000 V
■ Expected life	Mechanical	10 x 10 ⁶ ops.	20 x 10 ⁶ ops.	20 x 10 ⁶ ops.	500 x 10 ³ ops.
	Electrical (Rated load)	100 x 10 ³ ops. (VE) 50 x 10 ³ ops. (VE-S)	100 x 10 ³ ops.	100 x 10 ³ ops.	100 x 10 ³ ops.
■ Safety standards		UL, CSA, VDE	UL, CSA, VDE, IEC61010, 61131, CQC	UL, CSA, VDE, SEMKO, CQC, NEMKO, DEMKO, FIMKO	UL, TUV
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)		VE-M  VE 			
■ Remarks		* N.C. contact	- Right angle type available	- Flux-free type available - TV-5 rated	- 1.5mm contact gap - TV-3 rated






Power relays (5A~10A)

SERIES NAME		JV	LZ	FTR-F1	FTR-F1L
■ Dimensions W x L x H (mm)		 10.0 x 17.5 x 12.5	 16.4 x 21.4 x 14.8	 12.8 x 29.0 x 16.5	 12.8 x 29.0 x 16.5
■ Weight (approx.)		4.3 g	7.7 g	13.0 g	13.0 g
■ Contact form		1 a	1 a, 1 c	2 a, 2 c	2 a, 2 c
■ Contact current rating		5A, 10A	1A, 3A, 5A, 3A, 5A, 10A	5A, 8A	8A
■ Minimum switching load (ref.)		5VDC 100mA	5VDC 100mA, 5VDC 10mA, 100mVDC 0.1mA	5VDC 10mA	15VDC 10mA
■ Contact rating (Resistive load)		5A, 250VAC/30VDC 10A, 250VAC/24VDC	1A, 120VAC/30VDC 3A, 120VAC/30VDC 5A, 120VAC/24VDC 10A, 120VAC/24VDC	5A, 250VAC/24VDC 8A, 250VAC/24VDC	8A, 250VAC/24VDC
■ Coil voltage (DC)		3 to 48 V	1.5 to 24 V (48*, 100*)V	1.5 to 48 V	5 to 24 V
■ Nominal coil power		0.2 W / 0.3 W	0.33 W / 0.45 to 0.6 W	0.4 to 0.53 W	0.6 W
■ Dielectric strength	Open contacts	750 VAC	750 VAC	1,000 VAC	1,000 VAC
	Coil and contacts	5,000 VAC	2,000 VAC	5,000 VAC	5,000 VAC
■ Surge strength (Coil and contacts)		10,000 V	4,000 V / 6,000 V	10,000 V	10,000 V
■ Expected life	Mechanical	5 x 10 ⁶ ops.	20 x 10 ⁶ ops.	20 x 10 ⁶ ops.	3 x 10 ⁶ ops.
	Electrical (Rated load)	100 x 10 ³ ops.	100 x 10 ³ ops.	100 x 10 ³ ops.	50 x 10 ³ ops.
■ Safety standards		UL, CSA, VDE, SEMKO, CQC	UL, CSA	UL, CSA, VDE, SEMKO, NEMKO, DEMKO, BSI, FIMKO, IMQ	UL, CSA, VDE
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)					
■ Remarks		- High sensitive type available - 10 A type JV-KS	* Only standard type - Not for new designs	- Pin compatible with VB series - TV-3 rating available - Clear cover available	- 1 and 2 coil versions - Latching type





Power relays (6A~8A)

SERIES NAME		FTR-LY	JS	JS-RW New design	JSL
■ Dimensions W x L x H (mm)		 5.0 x 28.0 x 15.0	 10.0 x 29.0 x 12.5	 10.0 x 29.0 x 12.5	 10.0 x 29.0 x 12.5
■ Weight (approx.)		5.0 g	8.0 g	8.0 g	8.0 g
■ Contact form		1 a, 1 c	1 a, 1 c	1 a, 1 c	1 a
■ Contact current rating		6A	8A (10A carry)	8A (10A carry)	8A (10A carry)
■ Minimum switching load (ref.)		5VDC 10mA	5VDC 10mA	5VDC 100mA	5VDC 8mA
■ Contact rating (Resistive load)		6A, 250VAC/30VDC	8A, 250VAC/24VDC	8A, 250VAC/24VDC	8A, 250VAC/24VDC
■ Coil voltage (DC)		3 to 48 V	5 to 60 V	5 to 60 V	3 to 60 V
■ Nominal coil power		0.17 W / 0.21 W	0.22 to 0.29 W	0.22 to 0.29 W	0.22 to 0.25 W
■ Dielectric strength	Open contacts	1,000 VAC	1,000 VAC	1,000 VAC	1,000 VAC
	Coil and contacts	4,000 VAC	5,000 VAC	5,000 VAC	5,000 VAC
■ Surge strength (Coil and contacts)		6,000 V	10,000 V	10,000 V	10,000 V
■ Expected life	Mechanical	10 x 10 ⁶ ops.	20 x 10 ⁶ ops.	20 x 10 ⁶ ops.	20 x 10 ⁶ ops.
	Electrical (Rated load)	30 x 10 ³ ops. to 60 x 10 ³ ops.	50 x 10 ³ ops. to 60 x 10 ³ ops.	50 x 10 ³ ops. to 60 x 10 ³ ops.	100 x 10 ³ ops.
■ Safety standards		UL, CSA, VDE, SEMKO, NEMKO, DEMKO, FIMKO	UL, CSA, VDE, SEV, OVE, BSI, SEMKO, FIMKO, CQC, NEMKO, DEMKO	Pending	UL, CSA, VDE
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)		Through hole type  Right angle type 	JS-MK, JS-M()-KT  JS-K 	JS-MK, JS-M()-KT  JS-K 	
■ Remarks		- Ultra slim - Socket version available - Right angle type available	- 1000W lamp load type available (Inrush 64A) (JS-MN(-)-KS)	- Reflow solderable relay (RTH)	- 1 and 2 coil versions available - Latching type





Power relays (10A)

SERIES NAME		FTR-H1	FTR-H2	FTR-H3	FTR-J2
■ Dimensions W x L x H (mm)		 12.8 x 28.0 x 16.5	 11.0 x 24.0 x 25.0	 13.7 x 28.8 x 18.8	 23.5 x 24.0 x 27.0
■ Weight (approx.)		12.0 g	12.0 g	13.0 g	26.0 g
■ Contact form		1 a, 1 c	1 a	1 a	2 x 1 a, 1 x 1 a
■ Contact current rating		10A (14A carry)	10A	10A (14A carry)	10A
■ Minimum switching load (ref.)		5VDC 10mA	5VDC 100mA	5VDC 10mA	10VDC 100mA
■ Contact rating (Resistive load)		10A, 250VAC/30VDC	10A, 250VAC/30VDC	10A, 250VAC/30VDC TV-5/TV-8	10A, 200VDC x 2 10A, 450VDC
■ Coil voltage (DC)		5 to 48 V	5 to 48 V	5 to 48 V	10 to 110 V
■ Nominal coil power		0.4 to 0.53 W	0.25 to 0.53 W	0.53 W	0.53 to 1.06 W
■ Dielectric strength	Open contacts	1,000 VAC	1,000VAC	1,000 VAC	1,000 VAC
	Coil and contacts	5,000 VAC	4,000 VAC	5,000 VAC	4,000 VAC
■ Surge strength (Coil and contacts)		10,000 V	10,000 V	10,000 V	10,000 V
■ Expected life	Mechanical	20 x 10 ⁶ ops.	20 x 10 ⁶ ops.	20 x 10 ⁶ ops.	2 x 10 ⁶ ops.
	Electrical (Rated load)	100 x 10 ³ ops.	100 x 10 ³ ops.	100 x 10 ³ ops.	10 x 10 ³ ops.
■ Safety standards		UL, CSA, VDE, SEMKO, BSI, CQC, NEMKO, FIMKO, DEMKO	UL, CSA, VDE, SEMKO, NEMKO, DEMKO, FIMKO, CQC	UL, CSA VDE, CQC	VDE
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)		FTR-H1A  FTR-H1C 			Short circuit on PCB 
■ Remarks		- TV-5 rating available - Clear cover available	- Flux-free type available - TV-5 rated	- Pin compatible with FTR-H1 series (1 form A) - Low noise level 50dB - TV-8 rating available	- Special arc extinguishing provision





Power relays (10A~20A)

SERIES NAME		FTR-K1	FTR-K1L	FTR-K2	FTR-K2G
■ Dimensions W x L x H (mm)		 12.7 x 29.0 x 15.7	 12.7 x 29.0 x 15.7	 11.0 x 24.0 x 25.0	 16.0 x 35.0 x 28.0
■ Weight (approx.)		13.0 g	14.0 g	13.0 g	33.0 g
■ Contact form		1 a, 1 c	1 a, 1 c	1 a	1 a
■ Contact current rating		(14A carry) (20A carry) 10A 16A 17A	16A	16A	20A (25A carry)
■ Minimum switching load (ref.)		5VDC 10mA	5VDC 10mA	5VDC 100mA	5VDC 100mA
■ Contact rating (Resistive load)		10A, 250VAC 16A, 250VAC/24VDC 17A, 250VAC/24VDC (TAB-terminals)	16A, 250VAC (inrush 80A)	16A, 250VAC/(125VAC)/ 30VDC	20A, 250VAC
■ Coil voltage (DC)		5 to 48 V	5 to 24 V	5 to 48 V	5 to 110 V
■ Nominal coil power		0.4 W	0.4 W	0.53 W	1.1 W
■ Dielectric strength	Open contacts	1,000 VAC	1,000 VAC	1,000 VAC	2,000 VAC
	Coil and contacts	5,000 VAC	5,000 VAC	4,000 VAC	5,000 VAC
■ Surge strength (Coil and contacts)		10,000 V	10,000 V	10,000 V	10,000 V
■ Expected life	Mechanical	20 x 10 ⁶ ops.	3 x 10 ⁶ ops.	20 x 10 ⁶ ops.	10 x 10 ⁶ ops.
	Electrical (Rated load)	20 x 10 ³ ops. to 150 x 10 ³ ops.	100 x 10 ³ ops. 50 x 10 ³ ops.	100 x 10 ³ ops.	100 x 10 ³ ops.
■ Safety standards		UL, CSA, VDE, SEMKO, NEMKO, DEMKO, FIMKO	UL, CSA, VDE, SEMKO	UL, CSA, VDE, SEMKO, CQC	UL, CSA, VDE
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)					
■ Remarks		- High sensitive, 105°C type, clear cover, 120A and TAB-terminals available (17A) - Sealed versions available - 120A inrush type available - AC coil version under development	- 1 and 2 coil versions available - Latching type	- TV-5 and TV-8 rated	- TV-8 rated - 3mm contact gap



Power relays (20A~25A)

SERIES NAME		FTR-K3	FTR-K3-WG	FTR-K3L	FTR-K3-WS
■ Dimensions W x L x H (mm)		 15.7 x 30.1 x 23.3	 15.7 x 30.1 x 23.3	 15.7 x 30.1 x 23.3	 15.7 x 30.1 x 23.3
■ Weight (approx.)		25.0 g	25.0 g	25.0 g	26.0 g
■ Contact form		1 a	1 a	1 a	1 a
■ Contact current rating		20A, 25A	25A	25A (30A carry)	25A
■ Minimum switching load (ref.)		5VDC 100mA	5VDC 100mA	5VDC 100mA	5VDC 100mA
■ Contact rating (Resistive load)		20A, 250VAC	25A, 250VAC	25A, 250VAC	25A, 250VAC
■ Coil voltage (DC)		5 to 48 V	5 to 48 V	5 to 24 V	5 to 48 V
■ Nominal coil power		0.78 W	0.78 W	0.9 W	1.2 W
■ Dielectric strength	Open contacts	1,000 VAC	2,500 VAC	1,000 VAC	2,500 VAC
	Coil and contacts	5,000 VAC	5,000 VAC	5,000 VAC	5,000 VAC
■ Surge strength (Coil and contacts)		8,500 V	8,500 V	8,500 V	8,500 V
■ Expected life	Mechanical	20 x 10 ⁶ ops.	2 x 10 ⁶ ops.	1 x 10 ⁶ ops.	100 x 10 ³ ops.
	Electrical (Rated load)	100 x 10 ³ ops.	30 x 10 ³ ops.	100 x 10 ³ ops.	30 x 10 ³ ops.
■ Safety standards		UL, CSA, VDE, CQC	UL, VDE, CQC	UL, VDE	UL, VDE
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)		 (BOTTOM VIEW)			
■ Remarks		- TAB-terminals - Flat type available (FTR-K3F series, 25A)	- 1.5mm contact gap - 2 coils latching type available (FTR-K3L-WG)	- 2 coils latching type	- 1.8 mm contact gap





Power relays (30A~32A)

SERIES NAME		FTR-K3-PV	FTR-K3-PS	FTR-K3LV	FTR-K2W
■ Dimensions W x L x H (mm)		 15.7 x 30.1 x 23.3	 15.7 x 30.1 x 23.3	 15.7 x 30.1 x 23.3	 16.0 x 35.0 x 28.0
■ Weight (approx.)		25.0 g	26.0 g	27.0 g	70.0 g
■ Contact form		1 a	1 a	1 a	1 a
■ Contact current rating		32A (32A carry)	32A	32A	30A
■ Minimum switching load (ref.)		5VDC 100mA	5VDC 100mA	5VDC 100mA	5VDC 100mA
■ Contact rating (Resistive load)		32A, 250VAC	32A, 250VAC	32A, 250VAC	30A, 60VDC
■ Coil voltage (DC)		5 to 48 V	5 to 48 V	5 to 48 V	6 to 48 V
■ Nominal coil power		1.2 W	1.4 W	0.6 / 1.2 W	2 W
■ Dielectric strength	Open contacts	2,500 VAC	2,500 VAC	2,500 VAC	2,000 VAC
	Coil and contacts	5,000 VAC	4,000 VAC	4,000 VAC	5,000 VAC
■ Surge strength (Coil and contacts)		6,000 V	6,000 V	6,000 V	10,000 V
■ Expected life	Mechanical	1 x 10 ⁶ ops.	100 x 10 ³ ops.	1 x 10 ⁶ ops.	2 x 10 ⁶ ops.
	Electrical (Rated load)	30 x 10 ³ ops.	30 x 10 ³ ops.	30 x 10 ³ ops.	100 x 10 ³ ops.
■ Safety standards		UL, VDE	UL, VDE	Pending	Pending
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)					
■ Remarks		- High capacity 32A - 1.5mm contact gap - 2 coils latching type available (FTR-K3L-PV)	- 1.8 mm contact gap	- Screw hole terminals for contacts	- 2 x 3mm contact gap total 6mm







Power relays (120A)

SERIES NAME		FTR-V2	FTR-K4
■ Dimensions W x L x H (mm)		 70.0 x 62.0 x 23.0	New design  37.0 x 43.0 x 22.0
■ Weight (approx.)		120.0 g	80.0 g
■ Contact form		1 a	1 a
■ Contact current rating		120A (200A carry)	120A
■ Minimum switching load (ref.)		6VDC 1A	-
■ Contact rating (Resistive load)		120A, 277VAC 1,200A inrush	120A, 277VAC
■ Coil voltage (DC)		12 V	6 to 48 V
■ Nominal coil power		4.5 W	2.4 W (single winding) 4.8 W (double winding)
■ Dielectric strength	Open contacts	2,000 VAC	2,000 VAC
	Coil and contacts	4,000 VAC	4,000 VAC
■ Surge strength (Coil and contacts)		12,000 V	12,000 V
■ Expected life	Mechanical	200 x 10 ³ ops.	1 x 10 ⁶ ops.
	Electrical (Rated load)	1,000 ops. 240VAC/80A 1,000 ops. 100VAC/120A 120 x 10 ³ ops. inrush 230A make -1A break	5 x 10 ³ ops.
■ Safety standards		Pending	Pending
■ Mounting		Through hole	Through hole
■ Terminal layout (Bottom view)			
■ Remarks		- 120A latching relay - High current wide terminal - Dual coil latching type - Contact Fujitsu for details	- 120A latching relay



Signal relays (1A~2A)

SERIES NAME		SY	MZ	RY	A
■ Dimensions W x L x H (mm)		 7.4 x 12.5 x 9.5	 11.4 x 15.4 x 11.0	 9.8 x 20.2 x 12.5	 9.4 x 14.0 x 5.0
■ Weight (approx.)		1.7 g	3.5 g	5.0 g	1.2 g
■ Contact form		1 c	1 c	2 c	2 c
■ Contact current rating		(2A carry) 1A 1A	(2A carry) 1A 1A 2A	1A (1.25A carry) 2A (2A carry)	2A (2A carry)
■ Minimum switching load (ref.)		100mVDC 0.1mA 1VDC 1mA	100mVDC 0.01mA 1VDC 1mA	10mVDC 0.01mA	10mVDC 0.01mA
■ Contact rating (Resistive load)		0.5, 120VAC (SY) 1A, 24VDC 0.5A, 60VAC (SY-W) 1A, 24VDC	0.5A, 120VAC (MZ-W) 1A, 24VDC (MZ) 1A, 120VAC (MZ-D) 2A, 24VDC (MZ-D)	0.5A, 120VAC (RY-W, WZ) 1A, 24VDC 0.25A, 120VAC (RY-WF) 1A, 24VDC 0.5A, 125VAC (RY-WFZ) 2A, 30VDC	0.5A, 125VAC 1A, 30VDC
■ Coil voltage (DC)		1.5 to 24 V	1.5 to 48 V	4.5 to 48 V	1.5 to 24 (48*) V
■ Nominal coil power		0.15 to 0.175 W	0.19 to 0.27 W / 0.45 to 0.50W	0.15 to 0.58 W	0.2 to 0.3 W
■ Dielectric strength	Open contacts	300 VAC 400 VAC	500 VAC	500 VAC (W, WZ, WFZ) 1,000 VAC (WF)	1,000 VAC
	Coil and contacts	1,000 VAC	500 VAC / 1,000 VAC (MZ-F)	1,000 VAC	1,000 VAC
■ Surge strength (Coil and contacts)		1,500 V	1,500 V	1,500 V	1,500 V
■ Expected life	Mechanical	5 x 10 ⁶ ops.	20 x 10 ⁶ ops.	20 x 10 ⁶ ops. (W) 10 x 10 ⁶ ops. (WF, WZ, WFZ)	100 x 10 ⁶ ops. (A) 10 x 10 ⁶ ops. (AL, AL-D)
	Electrical (Rated load)	100 x 10 ³ ops.	200 x 10 ³ ops. (DC) 500 x 10 ³ ops. (AC)	100x10 ³ ops. (DC 30V,2A)* ₁ 200x10 ³ ops. (AC 120V,0.5A)* ₂ 500x10 ³ ops. (DC 24V,1A / AC 120V, 0.25A)	500 x 10 ³ ops. (DC) 50 x 10 ³ ops. (AC)
■ Safety standards		UL, CSA, FCC68	UL, CSA, FCC68	UL, CSA, FCC68	UL, CSA, FCC68
■ Mounting		Through hole	Through hole	Through hole	Through hole
■ Terminal layout (Bottom view)					
■ Remarks			- Not for new designs	*1: 2 Amp type *2: 1 Amp type	- 1 and 2 coil versions available - Latching type available * Only standard type


Signal relays (2A)

SERIES NAME		NA	FTR-B3	FTR-B4	FTR-C1
■ Dimensions W x L x H (mm)		 7.4 x 14.9 x 9.7	 7.2 x 10.6 x 5.45*	 5.7 x 10.6 x 9.0	 7.5 x 15.0 x 9.3
■ Weight (approx.)		1.6 g	0.85 g	1.0 g	2.0 g
■ Contact form		2 c	2 a	2 c	2 c
■ Contact current rating		2A (2A carry)	2A (2A carry)	2A (2A carry)	2A (2A carry)
■ Minimum switching load (ref.)		10mVDC 0.01mA	10mVDC 0.01mA	10mVDC 0.01mA	10mVDC 0.01mA
■ Contact rating (Resistive load)		0.5A, 125VAC 1A, 30VDC	0.3A, 125VAC 1A, 30VDC	0.3A, 125VAC 1A, 30VDC	0.3A, 125VAC 1A, 30VDC
■ Coil voltage (DC)		1.5 to 24V (*48 V)	1.5 to 24 V	1.5 to 24 V	3 to 24 V
■ Nominal coil power		0.1 to 0.3 W	0.1 to 0.23 W	0.1 to 0.23 W	0.14 to 0.3 W
■ Dielectric strength	Open contacts	1,000 VAC	1,000 VAC	1,000 VAC	1,500 VAC
	Coil and contacts	1,500 VAC (NA, NAL) 1,000 VAC (NAL-D)	1,500 VAC	1,500 VAC	3,000 VAC
■ Surge strength (Coil and contacts)		2,500 V (NA, NAL) 1,500 V (NAL-D)	2,500 V	2,500 V	5,000 V
■ Expected life	Mechanical	100 x 10 ⁶ ops. (NA) 10 x 10 ⁶ ops. (NAL, NAL-D)	50 x 10 ⁶ ops. (FTR-B3...A) 20 x 10 ⁶ ops. (FTR-B3...B)	50 x 10 ⁶ ops. 20 x 10 ⁶ ops. (latching)	10 x 10 ⁶ ops.
	Electrical (Rated load)	500 x 10 ³ ops. (DC) 200 x 10 ³ ops. (AC)	100 x 10 ³ ops.	200 x 10 ³ ops. (DC) 100 x 10 ³ ops. (AC)	100 x 10 ³ ops. (DC) 100 x 10 ³ ops. (AC)
■ Safety standards		UL, CSA, BSI, FCC68, Telcordia, IEC60950-1	UL, CSA, BSI, FCC68, Telcordia, IEC60950-1	UL, CSA, FCC68, Telcordia, IEC60950-1	UL, CSA, BSI, Telcordia
■ Mounting		Through hole	Through hole / surface mount	Through hole / surface mount	Through hole / surface mount
■ Terminal layout (Bottom view)		NA, NAL  NAL-D 			Standard  Latching 
■ Remarks		- Latching type available * Only standard type	- Latching type available * Through hole 7.2 x 10.6 x 5.2 mm	- Latching type available	- Latching type available - Contact gap 0.6 mm





Signal relays (2A)

SERIES NAME		FTR-C2
■ Dimensions W x L x H (mm)		 9.85 x 20.05 x 11.4
■ Weight (approx.)		3.7 g
■ Contact form		2 c
■ Contact current rating		2A (2A carry)
■ Minimum switching load (ref.)		10mVDC 0.01mA
■ Contact rating (Resistive load)		0.3A, 125VAC 1A, 30VDC
■ Coil voltage (DC)		3 to 12 V
■ Nominal coil power		0.3 W
■ Dielectric strength	Open contacts	1,500 VAC
	Coil and contacts	2,000 VAC
■ Surge strength (Coil and contacts)		2,500 V
■ Expected life	Mechanical	10 x 10 ⁶ ops.
	Electrical (Rated load)	100 x 10 ³ ops. (DC) 100 x 10 ³ ops. (AC)
■ Safety standards		UL, CSA, BSI, Telcordia, IEC60950-1
■ Mounting		Through hole / surface mount
■ Terminal layout (Bottom view)		Through hole  Surface mount 
■ Remarks		- 2mm contact gap



High frequency relays (0.3A/1A)

SERIES NAME		FTR-B3-RF
■ Dimensions W x L x H (mm)		 7.7 x 13.6 x 5.45
■ Weight (approx.)		1.3 g
■ Contact form		2 c
■ Contact current rating		1A0.3A
■ Minimum switching load (ref.)		30VDC125VAC
■ RF characteristics @ 50 Ω		3W @ 1GHz-switching 1W @ 1GHz-carry Isolation > 30dB @ 1GHz Insertion loss < 0.2dB @ 1 GHz V.S.W.R < 1.2 @ 1 GHz
■ Coil voltage (DC)		1.5 to 24V
■ Nominal coil power		0.1 W
■ Dielectric strength	Open contacts	750 VAC
	Coil and contacts	750 VAC
■ Surge strength (Coil and contacts)		1,500 V
■ Expected life	Mechanical	50 x 10 ⁶ ops.
	Electrical (Rated load)	100 x 10 ³ ops.
■ Safety standards		-
■ Mounting		Surface mount
■ Terminal layout (Bottom view)		
■ Remarks		- Latching type available

Solid state relays (1A~3A)

SERIES NAME			FTR-SL	SE	SG	SJ	
■ Dimensions W x L x H (mm)			 5.0 x 28.0 x 15.0	 5.0 x 20.0 x 17.0	 9.0 x 40.0 x 20.0	 10.0 x 20.0 x 12.8	
■ Weight (approx.)			4.0 g	4.0 g	13.0 g	5.5 g	
■ Type			-	-	-	-	
■ Voltage type			AC	AC	AC	AC	DC
■ Current			1.0 A	1.5 A	3.0 A	1 A	
■ Nominal voltage			5, 12, 24, 60 VDC	3, 5, 12, 24 VDC	3, 5, 12, 24 VDC	3,5,12,24 VDC	5,12,24 VDC
Input side	■ Impedance	3V	5 V: 560 Ω	180 Ω	130 Ω	120 Ω	-
		5V	12 V: 1.3k Ω	470 Ω	330 Ω	360 Ω	430 Ω
		12V	24V: 2.4k Ω	1.5k Ω	1.0k Ω	1.0k Ω	1.2k Ω
		24V	60V: 10k Ω	3.0k Ω	2.2k Ω	2.0k Ω	2.4k Ω
Output side	■ Load voltage range		AC 24 to 250 VAC rms	15 to 265 V rms	AC 75 to 265 V rms	24 to 265 V rms	3 to 30 VDC
	■ Max. load current		1.0 A rms	1.5 A rms	3.0 A rms	1.0 A rms	1.0 A
	■ Min. load current		1mA rms	10mA rms	10 mA rms	10 mA rms	1 mA
	■ 1 cycle surge current		50 A	50 A	132 A	50 A rms	3.0 A (10ms)
	■ Max. off-state leakage current		1 mA rms	0.5 / 1.0 mA rms	2.5 mA at 100 rms 5 mA at 200 rms	0.75/1.5 mA rms	0.1 mA
	■ Max. on-state voltage drop		1.3 V rms	1.2 V rms	1.5 V rms	1.2 V rms	1.2 V
■ Max. operate time			1/2 cycle + 1 ms	1 ms	1 ms	1 ms	
■ Max. release time			1/2 cycle + 1 ms	1/2 cycle + 1 ms	1/2 cycle + 1 ms	1/2 cycle + 1 ms	1 ms
■ Dielectric strength (Input-output)			2,500 V rms	2,500 V rms	2,500 V rms	2,500 V rms	
■ Operating temperature			-30°C to + 85°C	-30°C to + 85°C	-30°C to + 85°C	-30°C to + 85°C	
■ Storage temperature			-40°C to + 100°C	-40°C to + 100°C	-40°C to + 100°C	-40°C to + 100°C	
■ Safety standard			-	UL, CSA	UL, CSA	UL, CSA	
■ Mounting			Through hole	Through hole	Through hole	Through hole	
■ Terminal layout (Bottom view)						SJ-()A, SJ-()AN  SJ-()D, SJ-()DN 	
■ Remarks			- Pin compatible with FTR-LY - Internal zero cross circuit available - Internal varistor and snubber circuit	- Internal zero cross circuit available	- Internal zero cross circuit available - Internal output surge absorber (varistor) type available	- Pin compatible with JY - Internal surge absorber - Socket available	

Solid state relays (1A)

SERIES NAME			SN			
■ Dimensions W x L x H (mm)			 5.0 x 20.0 x 17.0			
■ Weight (approx.)			2.0 g	3.3 g	3.5 g	2.9 g
■ Type			Input module		Output module	
■ Voltage type			AC	DC	AC	DC
■ Current			-	-	1A	
■ Nominal voltage			100 VAC	12, 24 VDC	3,5,12,24 VDC	5, 12, 24 VDC
Input side	■ Impedance	3V	-	-	130/180 Ω	-
		5V	-	-	330/470Ω	390 Ω
		12V	-	-	1.0k/1.5k Ω	1.2k Ω
		24V	-	-	2.2k/3.8k Ω	2.4k Ω
Output side	■ Load voltage range		4 to 6 VDC		24 to 265 V rms	3 to 30 VDC
	■ Max. load current		±4 mA (VDD=5V)	±0.4 mA (VDD=5V)	1.0 A rms	1.0 A
	■ Min. load current		-	-	10 mA rms	1mA
	■ 1 cycle surge current		-	-	50 A	3 A (10ms)
	■ Max. off-state leakage current		-	-	1.5/3.0 mA rms	0.1 mA
	■ Max. on-state voltage drop		-	-	1.2 V rms	1.2 V
■ Max. operate time			25 ms	10 ms	1 ms	
■ Max. release time			30 ms	10 ms	1/2 cycle + 1ms	1 ms
■ Dielectric strength (Input-output)			2,500 V rms			
■ Operating temperature			-30°C to + 85°C			
■ Storage temperature			-40°C to + 100°C			
■ Safety standard			-			
■ Mounting			Through hole			
■ Terminal layout (Bottom view)			SN-A (input module)		SN-D (input module)	
			SN-A (output module)		SN-D (output module)	
■ Remarks			- Compatible with NY - Internal surge absorber - Socket available			

Notes

[illegible]

Notes

[illegible]

PRINCIPAL OFFICES OF FUJITSU COMPONENTS

EUROPE, MIDDLE EAST AND AFRICA

Headquarters

FUJITSU COMPONENTS EUROPE B.V.
Diamantlaan 25
2132 WV Hoofddorp
The Netherlands
Phone: +31-23-5560910
Fax: +31-23-5560950
Email: info@fceu.fujitsu.com
Website: emea.fujitsu.com/components/

THE AMERICAS

Headquarters

FUJITSU COMPONENTS AMERICA, INC.
250 E. Caribbean Drive
Sunnyvale, CA 94089
USA
Phone: 408-745-4900 / 800-380-0059
Fax: 408-745-4971
Email: components@us.fujitsu.com
Website: us.fujitsu.com/components/

ASIA PACIFIC

Headquarters

FUJITSU COMPONENTS ASIA PTE LTD.
102E Pasir Panjang Road
#01-01, Citilink Warehouse Complex
Singapore 118529
Phone: +65-6375-8560
Fax: +65-6273-3021
Email: fcsl@fcsl.fujitsu.com
Website: sg.fujitsu.com/components/

China

FUJITSU ELECTRONIC COMPONENTS
(Shanghai) Co., LTD.
Room 3106E, Bund Center,
222 Yan An Road (East)
Shanghai 200002 PRC
China
Phone: +86-21-63352560
Fax: +86-21-63352080

Hong Kong

FUJITSU COMPONENTS
HONG KONG CO., LTD.
Suite 913, Ocean Centre
5 Canton Road, TST
Kowloon
Hong Kong
Phone: +852-2881-8495
Fax: +852-2894-9412

Taiwan, Republic of China

FUJITSU COMPONENTS ASIA, LTD.
13th Fl, No. 178, Min Chuan E. Rd, Sec.3
Taipei
Taiwan
Phone: +886-2-2546-7587
Fax: +886-2-2546-8587

JAPAN

Headquarters

FUJITSU COMPONENT LIMITED
Gotanda-Chuo Building
3-5, Higashi-Gotanda 2-chome
Shinagawa-ku
Tokyo 141-8630
Japan
Phone: +81-3-5449-7010
Fax: +81-3-5449-2626
Email: promothq@fcl.fujitsu.com
Website: <http://www.fcl.fujitsu.com>



Published by

Fujitsu Components Europe b.v.

Diamantlaan 25, 2132 WV Hoofddorp, The Netherlands

Copyright: ©Fujitsu Components Europe b.v. 2012

Printed in The Netherlands

Order No.: PG-RL October 2012

Contact: info@fceu.fujitsu.com

All rights reserved, including rights created by patent grant or registration of a utility model. All designations used in this document may be trademarks, the use of which by third parties for their own purposes could violate the rights of their owners. We reserve the right to make modifications.

emea.fujitsu.com/components