

Fast Acting Fuses

Fast-acting fuses help provide overcurrent protection on systems using DC power sources up to 63V_{DC}. The fuse's monolithic, multilayer design provides the highest hold current in the smallest footprint, reduces diffusion-related aging, improves product reliability and resilience, and enhances high temperature performance. This helps facilitate the development of more reliable, high-performance consumer electronics such as laptops, multimedia devices, cell phones, and other portable electronics.



Benefits

- Small size with high current ratings
- Excellent temperature stability
- High reliability and resilience
- Strong arc suppression characteristics

Features

- RoHS compliant
- Monolithic, multilayer design
- High temperature performance
- -55°C to +125°C operating range

Applications

- | | | |
|-------------------|------------------------|----------------|
| • Laptops | • Printers | • Game systems |
| • Digital cameras | • DVD players | • LCD monitors |
| • Cell phones | • Portable electronics | • Scanners |


Table FF1 - Clear Time Characteristics for Fast Acting Fuses

% of rated current Clear time at 25°C

100%	4 hours min.
250%	5 seconds max.
400%	0.05 seconds max.


Table FF2 - Typical Electrical Characteristics, Dimensions and Recommended Pad Layout for Fast Acting Fuses

0402 (1005mm) Fast Acting Surface-mount Chip Fuses




Part Number	Typical Electrical Characteristics*		Max Interrupt Ratings*	
	Rated Current (A)	Nominal Cold DCR† (Ω)	Voltage (V _{DC})	Current (A)
0402SFF050F/24	0.50	0.380	24	35
0402SFF075F/24	0.75	0.210		
0402SFF100F/24	1.00	0.120		
0402SFF150F/24	1.50	0.056		
0402SFF200F/24	2.00	0.035		
0402SFF300F/24	3.00	0.021		
0402SFF400F/24	4.00	0.014		

0603 (1608mm) Fast Acting Surface-mount Chip Fuses



Part Number	Typical Electrical Characteristics*		Max Interrupt Ratings*	
	Rated Current (A)	Nominal Cold DCR† (Ω)	Voltage (V _{DC})	Current (A)
0603SFF050F/32	0.50	0.485	32	50
0603SFF075F/32	0.75	0.254		
0603SFF100F/32	1.00	0.131		
0603SFF150F/32	1.50	0.059		
0603SFF200F/32	2.00	0.044		
0603SFF250F/32	2.50	0.032		
0603SFF300F/32	3.00	0.025	24	35
0603SFF350F/32	3.50	0.024		
0603SFF400F/32	4.00	0.018		
0603SFF500F/32	5.00	0.013		
0603SFF600F/24	6.00	0.010		

1206 (3216mm) Fast Acting Surface-mount Chip Fuses



Part Number	Typical Electrical Characteristics*		Max Interrupt Ratings*	
	Rated Current (A)	Nominal Cold DCR† (Ω)	Voltage (V _{DC})	Current (A)
1206SFF050F/63	0.50	0.500	63	50
1206SFF075F/63	0.75	0.330		
1206SFF100F/63	1.00	0.220		
1206SFF150F/63	1.50	0.120		
1206SFF175F/63	1.75	0.100		
1206SFF200F/63	2.00	0.050		
1206SFF250F/32	2.50	0.035	32	45
1206SFF300F/32	3.00	0.031		
1206SFF400F/32	4.00	0.022		
1206SFF500F/32	5.00	0.015		
1206SFF600F/24	6.00	0.013	24	
1206SFF700F/24	7.00	0.011		
1206SFF800F/24	8.00	0.008		

* Measured at 25°C

† Measured at 10% of rated current



RoHS compliant, ELV compliant

Figures FF1-FF6 - Family Average Clear Time

Figure FF1 - 0402SFF Family Average Clear Time




Figure FF2 - 0402SFF Family I²T vs. Clear Time




Figure FF3 - 0603SFF Family Average Clear Time




Figure FF4 - 0603SFF Family I²T vs. Clear Time




Figure FF5 - 1206SFF Family Average Clear Time





Figure FF6 - 1206SFF Family I²t vs. Clear Time




Environmental Specifications

Operating Temperature	-55°C to +125°C
Mechanical Vibration	Withstands 5-3000 Hz at 30 Gs when evaluated per Method 204 of MIL-STD-202
Mechanical Shock	Withstands 1500 Gs, 0.5 millisecond half-sine pulses when evaluated per Method 213 of MIL-STD-202
Thermal Shock	Withstands 100 cycles from -65°C to +125°C when evaluated per Method 107 of MIL-STD-202
Resistance to Soldering Heat	Withstands 60 seconds at +260°C when evaluated per Method 210 of MIL-STD-202
Solderability	Meets 95% minimum coverage requirement when evaluated per Method 208 of MIL-STD-202
Moisture Resistance	Withstands 10 cycles when evaluated per Method 106 of MIL-STD-202
Salt Spray	Withstands 48-hour exposure when evaluated per Method 101 of MIL-STD-202

Material Specifications

Construction Body Material	Ceramic
Termination Material	Silver, Nickel, Tin
Fuse Element	Silver
Terminal Strength	Hanging test: 0603: 0.5kg 30 seconds; 1206 1.5kg, 30 seconds; 0402 part types meet 2-pound push test

Thermal Derating Current



Electrical Specifications

Insulation Resistance after Opening	20,000Ω minimum @ rated voltage. Fuse clearing under low voltage conditions may result in lower post-clearing insulation values. Under normal fault conditions values. Under normal fault conditions Raychem fuses provide sufficient insulation resistance for circuit protection.
Current Carrying Capacity	Withstands 100% rated current at +25°C ambient for 4 hours when evaluated per MIL-PRF-23419


Packaging Specifications

Chip Size	Parts on 7-inch (178 mm) Reel
0402 (1005)	10,000
0603 (1608)	4,000
1206 (3216)	3,000

Agency Approvals for Fast Acting Fuses

UL File # E197536

Part Numbering System for Fast Acting Fuses



WARNING:

All information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics Corporation makes no warranties as to the accuracy or completeness of the information, and disclaims any liability regarding its use. Tyco Electronics' only obligations are those in the Company's Standard Terms and Conditions of Sale for this product, and in no case will Tyco Electronics be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of the product. Specifications are subject to change without notice. In addition, Tyco Electronics reserves the right to make changes without notification to Buyer—to materials or processing that do not affect compliance with any applicable specification.