

Specification Status: RELEASED

Max Electrical Rating at 20°C



Operating Voltage: 60V_{DC}

Interrupt Current: 3A_{RMS}

Fault Voltage: 250V_{RMS}

Lead Material : 22 AWG Sn plated copper

Marking:



(Center-to-Center)

TABLE I. DIMENSIONS

	A		B		C		D		E
	Min	Max	Min	Max	Min	Max	Min	Max	Nom
mm:	--	5.8	--	9.9	--	4.6	4.7	--	5.0
in*:	--	(0.228)	--	(0.390)	--	(0.181)	(0.185)	--	(0.197)

TABLE II. PERFORMANCE RATINGS @ 20°C (unless otherwise noted):

I _{HOLD} (A)	I _{TRIP} (A)	RESISTANCE (Ω) @ 20°C			TIME TO TRIP (s) @ 0.35A	OPERATING TEMPERATURE (°C)	
		R MIN	R MAX	R _{1 MAX} *		MIN	MAX
20°C	20°C				MAX		
0.080	0.160	15	22	33	4	-40	85

* Maximum device resistance at 20° C measured 1 hour post trip.

Agency Recognition: UL, CSA, TUV pending
 Reference Documents: PS300
 Precedence: This specification takes precedence over documents referenced herein.
 Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.
 CAUTION: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.

Materials Information

ROHS Compliant

Directive 2002/95/EC
 Compliant

ELV Compliant

Directive 2000/53/EC
 Compliant

Pb-Free

