

Specification Status: Released

Max Electrical Rating at 20°C

Operating Voltage: 60V_{DC}
Interrupt Current: 3A_{RMS}

Fault Voltage: 250V_{RMS}

Lead Material : 22 AWG Sn plated copper

Marking:

- Raychem Logo
- X** 20 Part Identification
- □ □ Lot Identification




TABLE I. DIMENSIONS:

A		B		C		D		E	F		
Min	Max	Min	Max	Min	Max	Min	Max	Nom	Min	Max	
mm:	--	6.0	--	10.0	--	3.8	4.7	--	5.0	--	6.0
in:	--	(0.236)	--	(0.394)	--	(0.150)	(0.185)	--	(0.197)	--	(0.236)

TABLE II. PERFORMANCE RATINGS @ 20°C (unless otherwise noted):

IHOLD (A)	ITRIP (A)	RESISTANCE (Ω) @ 20°C			TIME TO TRIP (s) @ 1A		OPERATING TEMPERATURE (°C)		
		R MIN	R MAX	R _{1 MAX} *	TYP	MAX	MIN	MAX	
20°C	20°C								
0.120	0.240	6.0	10.0	16.0	1.0	2.0	-40	85	

*Maximum device resistance at 20°C measured 1 hour post trip.

Additional Rating @ 20°C

Lightning Withstand: ITU AT 1.5kV

Agency Recognition: UL, CSA, TUV pending

Reference Documents: PS300

Precedence: This specification takes precedence over documents referenced herein.

Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.

CAUTION: Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame

ROHS Compliant

ELV Compliant

Pb-Free

Directive 2002/95/EC
Compliant

Directive 2000/53/EC
Compliant

